Sandflex mottling points

SFM 656

Properties

Bonding agent	Plastic
Grain	SiC

Materials

Stainless steel	●

Product benefit

Produces a glossy finish on stainless steel surfaces - Soft abrasion due to elastic structure - Available in two executions: with flattened shaft for simple and secure clamping (standard execution, stock items) and with full length round shaft (made to order items)

Applications

- Apparatus and container manufacturing

Available grits:

16 20 24 30 36 40 50 60 80 100 120 150 180 220 240 280 320 360 400 500 600 800 1000 1200 1500 2000 2500 3000

Diameter x Height x Shaft in mm	grain	Bond	Vmax m/s	Max. RPM	Packing unit/pcs.	Cat. number
30 x 30 x 6	60	T	5 m/s	3200 rpm	10	334988
30 x 30 x 6	120	T	5 m/s	3200 rpm	10	334990
40 x 30 x 6	60	T	5 m/s	2400 rpm	10	334991
40 x 30 x 6	120	T	5 m/s	2400 rpm	10	334992
50 x 30 x 6	60	T	5 m/s	1900 rpm	10	334993
50 x 30 x 6	120	T	5 m/s	1900 rpm	10	334994

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de