
SCM disc, waterproof

NDS 800







Properties

Bonding agent	Resin
Grain	Aluminium oxide

Product benefit

High edge stability - Aggressive abrasive behaviour - Long service life - Can be used for wet and dry grinding - With expressible center hole for easy mounting, secure hold and smooth running on backing plates with centering - Also suited for backing pads without centering and fiber discs backing plates with clamping screw

Materials

Metals	●
Stainless steel	●
Paint/Varnish/Filler	◑
Plastic	◑
Wood	◑

Applications

- Stainless steel processing industry
- Metal construction
- Apparatus and container manufacturing

Available grits:

16 24 30 36 40 **50** 60 80 **100** 120 150 **180** 220 240 280 320 360 400 500 600 800 1000 1200 1500 2000 2500 3000

Diameter x Bore in mm	Grit	Colour	Grade	Packing unit/pcs.	Cat. number
125 x 22	50	brown	coarse	10	320106
125 x 22	100	maroon	medium	10	320107
125 x 22	180	blue	very fine	10	320108
180	50	brown	coarse	10	262136
180	100	maroon	medium	10	262138

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de