Wheel brush, crimped wire

BR 600 W





Product benefit

Suitable for low to medium duty brushing and deburring of cut edges, tubes or small parts - Ø150-200 mm for use on stationary machines - Ø115/Ø125 mm for use on angle grinders - High fill density for a long service life - Incl. adapter set for brushes Ø 150 - 200 mm to reduce the mounting hole (12,7 mm, 16 mm, 19 mm, 22,2 mm, 25,4 mm)

Materials

Steel	●
Stainless steel	●

Applications

- Metal construction
- Locksmith's shop
- Stainless steel processing industry

Diameter x Width x Bore in mm	Fill material	Wire thickness in mm	Fill length in mm	Max. RPM	Packing unit/pcs.	Cat. number
150 x 25 x 32	Steel	0,30	30	6000 rpm	1	363997
150 x 25 x 32	Stainless steel	0,30	30	6000 rpm	1	364000
200 x 25 x 32	Steel	0,30	45	4500 rpm	1	363999
200 x 25 x 32	Stainless steel	0,30	45	4500 rpm	1	364002

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de