# Wheel brush with shaft, crimped wire

# BRS 600 W



## Product benefit

Crimped wire design for gentle cleaning of small to medium surfaces - Excellently suitable for components with difficult access such as beads, flanged edges - Good brushing performance even with profiled workpieces. Suitable for rapid runners.

## Materials

| | |
|---|---|
| Steel | ● |
| Stainless steel | ● |

## Applications

- Plant engineering
- Apparatus and container manufacturing
- Stainless steel processing industry
- Railing construction
- Metal construction
- Steel construction
- Locksmith's shop

| Diameter x Width x Shaft in mm | Total length in mm | Fill material | Wire thickness in mm | Fill length in mm | Max. RPM | Packing unit/pcs. | Cat. number |
|---|---|---|---|---|---|---|---|
| 30 x 9 x 6 | 40 | Steel | 0,20 | 6 | 20000 rpm | 20 | 358346 |
| 30 x 9 x 6 | 40 | Stainless steel | 0,20 | 6 | 20000 rpm | 20 | 358357 |
| 40 x 9 x 6 | 40 | Steel | 0,20 | 11 | 18000 rpm | 20 | 358348 |
| 40 x 9 x 6 | 40 | Stainless steel | 0,20 | 11 | 18000 rpm | 20 | 358358 |
| 50 x 9 x 6 | 40 | Steel | 0,30 | 13 | 15000 rpm | 10 | 358354 |
| 50 x 9 x 6 | 40 | Stainless steel | 0,30 | 13 | 15000 rpm | 10 | 358359 |

**Klingspor Schleifsysteme GmbH und Co. KG**
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de

| Diameter x Width x Shaft in mm | Total length in mm | Fill material | Wire thickness in mm | Fill length in mm | Max. RPM | Packing unit/pcs. | Cat. number |
|---|---|---|---|---|---|---|---|
| 60 x 14 x 6 | 44 | Steel | 0,30 | 18 | 15000 rpm | 10 | 358355 |
| 60 x 14 x 6 | 44 | Stainless steel | 0,30 | 18 | 15000 rpm | 10 | 358360 |
| 70 x 16 x 6 | 48 | Steel | 0,30 | 20 | 15000 rpm | 10 | 358356 |
| 70 x 16 x 6 | 48 | Stainless steel | 0,30 | 20 | 15000 rpm | 10 | 358362 |

**Klingspor Schleifsysteme GmbH und Co. KG**
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de